Ultra-weak symmetry of stress for augmented mixed finite element formulations in continuum mechanics^{*}

Javier A. Almonacid[†] Gabriel N. Gatica[‡] Ricardo Ruiz-Baier[§]

Abstract

In this paper we propose a novel way to prescribe weakly the symmetry of stress tensors in weak formulations amenable to the construction of mixed finite element schemes. The approach is first motivated in the context of solid mechanics (using, for illustrative purposes, the linear problem of linear elasticity), and then we apply this technique to reduce the computational cost of augmented fully-mixed methods for the thermal convection problems in fluid mechanics, in the case where several additional variables are defined. We show that the new approach allows to maintain the same structure of the mathematical analysis as in the original formulations. Therefore we only need to focus on coercivity of certain bilinear forms, as this property provides feasible ranges for the stabilization parameters that complete the description of augmented methods. In addition, we present some numerical examples to show that these methods perform better than their counterparts that include vorticity, and emphasize that the reduction in degrees of freedom (and therefore, in computational cost) does not affect the quality of numerical solutions.

Key words: Mixed finite element methods; ultra-weakly imposed symmetry; linear elasticity; Boussinesq equations; a priori error estimates.

Mathematics subject classifications (2000): 65N30; 74S05; 76M10; 65N15.

1 Introduction

There is no doubt that the devise of numerical methods for problems in elastostatics and fluid mechanics is an active research area in Numerical Analysis (see, e.g., [1, 2, 3, 6, 10, 11, 13] and the references therein), and even when we have substantially different models for each of these areas (for instance, the linear elasticity and Navier-Stokes equations), one variable that is present in both contexts is the Cauchy stress σ , a second order tensor that describes the state of stress at a point inside a material in the deformed state. In many applications σ is symmetric, and therefore, numerical methods must take into account this property. For the case of finite element methods, this is imposed either strongly

^{*}This research was partially supported by CONICYT-Chile through the project AFB170001 of the PIA Program: Concurso Apoyo a Centros Científicos y Tecnológicos de Excelencia con Financiamiento Basal, and Fondecyt project 1161325; by Centro de Investigación en Ingeniería Matemática (CI²MA), Universidad de Concepción; and by the Oxford Centre for Doctoral Training in Industrially Focused Mathematical Modelling.

[†]Centro de Investigación en Ingeniería Matemática (CI²MA), Universidad de Concepción, Casilla 160-C, Concepción, Chile, email: jalmonacid@ci2ma.udec.cl. Present address: Department of Mathematics, Simon Fraser University, 8888 University Drive, Burnaby, BC V5A 1S6, Canada, email: javiera@sfu.ca.

[‡]CI²MA and Departamento de Ingeniería Matemática, Universidad de Concepción, Casilla 160-C, Concepción, Chile, email: ggatica@ci2ma.udec.cl.

[§]Mathematical Institute, University of Oxford, Woodstock Road, OX2 6GG Oxford, UK, email: ruizbaier@maths.ox.ac.uk.

(that is, the finite element is constructed in a way that only symmetric approximations are allowed) or weakly via a Lagrange multiplier. In this work we focus on the latter.

A number of methods have been proposed to obtain acceptable approximations of the stress tensor. On the one hand, a common finite element to approximate the stress tensor is given by a row-wise approximation using Raviart-Thomas elements. Since this leads to an unsymmetric tensor, the symmetry is imposed weakly by considering this variable orthogonal to all skew-symmetric tensors, which then requires to introduce the vorticity tensor (the skew-symmetric part of the displacement gradient, or velocity gradient in the context of fluid mechanics) as an additional unknown. This idea, attributed to [9] and later formalized by [5] and [15], can provide asymptotically symmetric approximations for the stress, using fewer degrees of freedom than finite elements with strong imposition of symmetry. On the other hand, augmented methods such as those proposed in [10, 11, 13] can provide finite elements that have even fewer degrees of freedom, at the cost of increasing the fullness of the resulting system matrix and, sometimes, increasing also the regularity of other variables, such as displacements or velocities (and in particular, relaxing compatibility conditions between approximation spaces).

Therefore, according to the above, here we propose and study an even weaker way to impose the symmetry of the stress, with the benefit of reducing the computational cost of augmented finite element methods. More precisely, we exploit the fact that, in many relevant applications, the symmetry of this tensor is given by its dependence on the strain or strain rate (the symmetric part of the displacement gradient or the velocity gradient tensors, respectively). In this way, we begin by describing this approach in the context of elastostatics taking [13] as a basis, to then reduce the computational cost of a method for the Boussinesq problem, taking this time [1] as a reference. On the one hand, we will see that some properties, such as bilinearity and boundedness of the involved operators, are a straightforward result of the analysis in the cited works; whereas the analysis of other features, such as coercivity, will need to be redone (but using essentially the same tools). We will also see that this method does not require an additional regularity of other variables, it decreases the number of degrees of freedom of the system, and it still provides stress tensors that are asymptotically symmetric. It is also worthwhile to mention that, in the context of an augmented mixed method for the Navier-Stokes equations, the results from [6] provide a vorticity-free method resulting from a double integration by parts (as a way to impose mixed boundary conditions). Even if that scheme already uses a weaker imposition of symmetry (but not precisely the same as done in this paper), the authors in such work do not address the implications that this change could bring.

1.1 Outline

The rest of this work is organized as follows. First, we end this section by introducing some notation that will be used throughout this work, and then in Section 2 we present this weaker imposition of the symmetry of the stress tensor, and the resulting vorticity-free version of the continuous formulations presented in [13] and [1] for the elasticity and Boussinesq problems, respectively. Here, we focus on proving coercivity of the bilinear forms, as this is the property that completely describes augmented methods. Next, in Section 3, we derive the corresponding Galerkin schemes for these formulations, to then in Section 4 present some numerical results that portray the main characteristics of the proposed augmented methods. Unless specified otherwise, the notation for spaces, finite dimensional subspaces, bilinear forms and functional are local to each problem.

1.2 Notation

Let us denote by $\Omega \subset \mathbb{R}^n$, $n \in \{2,3\}$, a given bounded, simply connected domain with polyhedral boundary Γ , and denote by $\boldsymbol{\nu}$ the outward unit normal vector on Γ . Standard notation will be adopted

for Lebesgue spaces $L^p(\Omega)$ and Sobolev spaces $W^{s,2}(\Omega) =: H^s(\Omega)$ with norm $\|\cdot\|_{s,\Omega}$ and seminorm $|\cdot|_{s,\Omega}$. In particular, $H^{1/2}(\Gamma)$ is the space of traces of functions in $H^1(\Omega)$. By **M** and **M** we will denote the corresponding vectorial and tensorial counterparts of the generic scalar functional space M, and $\|\cdot\|$, with no subscripts, will stand for the natural norm of either an element or an operator in any product functional space. In turn, for any vector fields $\mathbf{v} = (v_i)_{i=\overline{1,n}}$ and $\mathbf{w} = (w_i)_{i=\overline{1,n}}$, we set the gradient, divergence and tensor product operators, as

$$\nabla \mathbf{v} := \left(\frac{\partial v_i}{\partial x_j}\right)_{i,j=\overline{1,n}}, \quad \text{div}\,\mathbf{v} := \sum_{j=1}^n \frac{\partial v_j}{\partial x_j}, \quad \text{and} \quad \mathbf{v} \otimes \mathbf{w} := (v_i w_j)_{i,j=\overline{1,n}}.$$

In addition, for any tensor fields $\boldsymbol{\tau} = (\tau_{ij})_{i,j=\overline{1,n}}$ and $\boldsymbol{\zeta} = (\zeta_{ij})_{i,j=\overline{1,n}}$, we let $\operatorname{div} \boldsymbol{\tau}$ be the divergence operator div acting along the rows of $\boldsymbol{\tau}$, and define the transpose, the trace, the tensor inner product, and the deviatoric tensor, respectively, as

$$\boldsymbol{\tau}^{\mathsf{t}} := (\tau_{ji})_{i,j=\overline{1,n}}, \quad \operatorname{tr}(\boldsymbol{\tau}) := \sum_{i=1}^{n} \tau_{ii}, \quad \boldsymbol{\tau} : \boldsymbol{\zeta} := \sum_{i,j=1}^{n} \tau_{ij} \zeta_{ij}, \quad \text{and} \quad \boldsymbol{\tau}^{\mathsf{d}} := \boldsymbol{\tau} - \frac{1}{n} \operatorname{tr}(\boldsymbol{\tau}) \mathbb{I},$$

where I stands for the identity tensor in $\mathbb{R} := \mathbb{R}^{n \times n}$. Furthermore, we recall that any tensor can be (uniquely) decomposed into its symmetric and skew-symmetric parts. In particular, for $\nabla \mathbf{v}$ this means that there exists tensors $\mathbf{e}(\mathbf{v})$ and $\boldsymbol{\omega}(\mathbf{v})$ such that

$$\nabla \mathbf{v} = \mathbf{e}(\mathbf{v}) + \boldsymbol{\omega}(\mathbf{v}) \quad \text{where} \quad \mathbf{e}(\mathbf{u}) := \frac{1}{2} \left(\nabla \mathbf{v} + (\nabla \mathbf{v})^{\mathsf{t}} \right) \quad \text{and} \quad \boldsymbol{\omega}(\mathbf{v}) := \frac{1}{2} \left(\nabla \mathbf{v} - (\nabla \mathbf{v})^{\mathsf{t}} \right). \tag{1.1}$$

We also recall that

$$\mathbb{H}(\operatorname{\mathbf{div}};\Omega) := \Big\{ \boldsymbol{\tau} \in \mathbb{L}^2(\Omega) \, : \, \operatorname{\mathbf{div}} \boldsymbol{\tau} \in \mathbf{L}^2(\Omega) \Big\},\,$$

equipped with the usual norm

$$\| \, oldsymbol{ au} \, \|_{{f div};\Omega}^2 := \| \, oldsymbol{ au} \, \|_{0,\Omega}^2 + \| \, {f div} \, oldsymbol{ au} \, \|_{0,\Omega}^2,$$

is a standard Hilbert space in the realm of mixed problems. In addition, there holds the decomposition $\mathbb{H}(\mathbf{div}; \Omega) = \mathbb{H}_0(\mathbf{div}; \Omega) \oplus \mathbb{RI}$, where

$$\mathbb{H}_0(\operatorname{\mathbf{div}};\Omega) := \left\{ \boldsymbol{\tau} \in \mathbb{H}(\operatorname{\mathbf{div}};\Omega) : \int_{\Omega} \operatorname{tr}(\boldsymbol{\tau}) = 0 \right\}.$$

Finally, in what follows, $|\cdot|$ denotes the Euclidean norm in $\mathbf{R} := \mathbf{R}^n$, and we employ $\mathbf{0}$ to denote a generic null vector and use C, with or without subscripts, bars, tildes or hats, to mean generic positive constants independent of the discretization parameters, which may take different values at different places.

2 Continuous formulations with ultra-weak symmetry

We begin this section by recalling some results that will be used throughout this work to prove coercivity of bilinear forms, since this is indeed the property that define admissible values for the stabilization parameters. Other properties such as boundedness of the bilinear forms are usually valid for just non-negative values of these parameters.

Lemma 2.1. Let Ω be a bounded, simply connected domain with polyhedral boundary $\Gamma := \partial \Omega$. Then,

a) there exists $c_1 > 0$ such that

$$\|\boldsymbol{\tau}^{\mathsf{d}}\|_{0,\Omega}^{2} + \|\operatorname{\mathbf{div}}\boldsymbol{\tau}\|_{0,\Omega}^{2} \ge c_{1}\|\boldsymbol{\tau}_{0}\|_{0,\Omega}^{2} \quad \forall \boldsymbol{\tau} = \boldsymbol{\tau}_{0} + c\mathbb{I} \in \mathbb{H}(\operatorname{\mathbf{div}};\Omega), \, \boldsymbol{\tau}_{0} \in \mathbb{H}_{0}(\operatorname{\mathbf{div}};\Omega), \, c \in \mathbb{R}, \quad (2.1)$$

b) there exists $c_2 > 0$ such that

$$\|\mathbf{e}(\mathbf{v})\|_{0,\Omega}^2 \ge c_2 \|\mathbf{v}\|_{1,\Omega}^2 \quad \forall \ \mathbf{v} \in \mathbf{H}_0^1(\Omega),$$
(2.2)

with $c_2 = 0.5$ when $\Omega \subset \mathbb{R}^2$, and

c) there exists $c_3 > 0$ such that

$$\|\mathbf{e}(\mathbf{v})\|_{0,\Omega}^2 + \|\mathbf{v}\|_{0,\Gamma}^2 \ge c_3 \|\mathbf{v}\|_{1,\Omega}^2 \quad \forall \mathbf{v} \in \mathbf{H}^1(\Omega).$$

$$(2.3)$$

Proof. See [10, Lemma 2.1] for a), [14, Theorem 10.1] for b), [11, Lemma 3.1 and (3.9)] for c) when $\Omega \subset \mathbb{R}^2$, and [13, Lemma A.2] for c) when $\Omega \subset \mathbb{R}^3$.

2.1 Linear elasticity

To introduce this weaker imposition of the symmetry of the stress tensor, let us consider an isotropic linear material occupying the three-dimensional region Ω in the context of elastostatics. Then, a simple model to describe this problem seeks a displacement **u** and a stress tensor $\boldsymbol{\sigma}$ such that

$$\boldsymbol{\sigma} = \mathscr{C} \mathbf{e}(\mathbf{u}) \quad \text{in } \Omega, \qquad -\mathbf{div} \, \boldsymbol{\sigma} = \mathbf{f} \quad \text{in } \Omega, \qquad \mathbf{u} = \mathbf{u}_D \quad \text{on } \Gamma, \tag{2.4}$$

where $\mathbf{f} \in \mathbf{L}^2(\Omega)$ is a volume force, $\mathbf{e}(\mathbf{u})$ is the strain tensor of small deformations (defined as in (1.1)), $\mathbf{u}_D \in \mathbf{H}^{1/2}(\Gamma)$ is a given Dirichlet datum for \mathbf{u} , and \mathscr{C} is the elasticity tensor, which according to Hooke's Law is given by

$$\mathscr{C}\boldsymbol{\zeta} := \lambda \operatorname{tr}(\boldsymbol{\zeta}) \mathbb{I} + 2\,\mu\,\boldsymbol{\zeta} \quad \forall\,\boldsymbol{\zeta} \in \mathbb{L}^2(\Omega), \tag{2.5}$$

with λ , $\mu > 0$ being the corresponding Lamé constants. After a simple computation, it can be seen from this equation that the action of the compliance tensor is given by

$$\mathscr{C}^{-1}\boldsymbol{\zeta} = \frac{1}{2\mu}\boldsymbol{\zeta} - \frac{\lambda}{2\mu(2\mu + 3\lambda)} \operatorname{tr}(\boldsymbol{\zeta})\mathbb{I} \quad \forall \; \boldsymbol{\zeta} \in \mathbb{L}^2(\Omega).$$
(2.6)

In this way, considering $\mathbf{e}(\mathbf{u}) = \nabla \mathbf{u} - \boldsymbol{\omega}(\mathbf{u})$ as in (1.1), the elasticity equations (2.4) can be rewritten as

$$\mathscr{C}^{-1}\boldsymbol{\sigma} = \nabla \mathbf{u} - \boldsymbol{\omega}(\mathbf{u}) \quad \text{in } \Omega, \qquad -\mathbf{div}\,\boldsymbol{\sigma} = \mathbf{f} \quad \text{in } \Omega, \qquad \mathbf{u} = \mathbf{u}_D \quad \text{on } \Gamma.$$
 (2.7)

Then, a mixed formulation for this problem can be constructed by multiplying the first equation of (2.7) by a test function $\tau \in \mathbb{H}(\operatorname{div}; \Omega)$ and integrating by parts, while the second equation is just tested with $\mathbf{v} \in \mathbf{L}^2(\Omega)$. The next step is to include in the formulation the symmetry of the Cauchy stress tensor with an additional term.

Differently from other works (e.g. [5, 10, 13]), we will not define the vorticity as an additional variable to be computed. Moreover, we will not impose the symmetry of the stress tensor by considering it orthogonal (with respect to the standard L^2 inner product) to all skew-symmetric tensors in $L^2(\Omega)$ (weak imposition), but rather to only those that can be written as the skew-symmetric part of a velocity gradient, that is

$$\int_{\Omega} \boldsymbol{\sigma} : \boldsymbol{\omega}(\mathbf{v}) = 0 \quad \forall \ \mathbf{v} \in \mathbf{H}^{1}(\Omega).$$
(2.8)

We refer to the addition of this term to the formulation as an "ultra-weak" imposition of the symmetry of $\boldsymbol{\sigma}$. In this way, at a first glance, the mixed formulation for (2.7) is given by: Find $(\boldsymbol{\sigma}, \mathbf{u}) \in$ $\mathbb{H}(\mathbf{div}; \Omega) \times \mathbf{H}^1(\Omega)$ such that

$$\int_{\Omega} \mathscr{C}^{-1} \boldsymbol{\sigma} : \boldsymbol{\tau} + \int_{\Omega} \boldsymbol{\omega}(\mathbf{u}) : \boldsymbol{\tau} + \int_{\Omega} \mathbf{u} \cdot \mathbf{div} \, \boldsymbol{\tau} = \langle \, \boldsymbol{\tau} \boldsymbol{\nu}, \mathbf{u}_D \, \rangle_{\Gamma} \quad \forall \, \boldsymbol{\tau} \in \mathbb{H}(\mathbf{div}; \Omega),$$
(2.9a)

$$\int_{\Omega} \boldsymbol{\omega}(\mathbf{v}) : \boldsymbol{\sigma} + \int_{\Omega} \mathbf{v} \cdot \mathbf{div} \, \boldsymbol{\sigma} \qquad = -\int_{\Omega} \mathbf{f} \cdot \mathbf{v} \quad \forall \mathbf{v} \in \mathbf{H}^{1}(\Omega).$$
(2.9b)

The idea is to proceed with the analysis in the exact same terms as [13]. First, the stress tensor $\boldsymbol{\sigma}$ is decomposed as $\boldsymbol{\sigma} = \boldsymbol{\sigma}_0 + c\mathbb{I}$, with $\boldsymbol{\sigma}_0 \in \mathbb{H}_0(\operatorname{div}; \Omega)$ and $c \in \mathbb{R}$, which, taking $\boldsymbol{\tau} = \mathbb{I}$ in (2.9), yields the explicit knowledge of c in terms of \mathbf{u}_D . In this way, and after denoting the remaining unknown $\boldsymbol{\sigma}_0$ as simply $\boldsymbol{\sigma}$, we augment the formulation (2.9) with the following Galerkin-type terms:

$$egin{aligned} &\kappa_1 \int_\Omega \left\{ \mathbf{e}(\mathbf{u}) - \mathscr{C}^{-1} oldsymbol{\sigma}
ight\} : \left\{ \mathbf{e}(\mathbf{v}) + \mathscr{C}^{-1} oldsymbol{ au}
ight\} &= \kappa_1 \left(rac{1}{3|\Omega|} \int_{\Gamma} \mathbf{u}_D \cdot oldsymbol{
u}
ight) \int_{\Omega} \mathbb{I} : \left\{ \mathbf{e}(\mathbf{v}) + \mathscr{C}^{-1} oldsymbol{ au}
ight\}, \ &\kappa_2 \int_{\Omega} \mathbf{div} \, oldsymbol{\sigma} \cdot \mathbf{div} \, oldsymbol{ au} &= -\kappa_2 \int_{\Omega} \mathbf{f} \cdot \mathbf{div} \, oldsymbol{ au}, \ &\kappa_3 \int_{\Gamma} \mathbf{u} \cdot \mathbf{v} = \kappa_3 \int_{\Gamma} \mathbf{u}_D \cdot \mathbf{v}. \end{aligned}$$

for all $(\boldsymbol{\tau}, \mathbf{v}) \in \mathbb{H}_0(\operatorname{\mathbf{div}}; \Omega) \times \mathbf{H}^1(\Omega)$, with $\kappa_1, \kappa_2, \kappa_3 > 0$ positive stabilization parameters to be determined later on. Therefore, introducing the product space $\mathcal{H} := \mathbb{H}_0(\operatorname{\mathbf{div}}; \Omega) \times \mathbf{H}^1(\Omega)$, the augmented mixed formulation of the elasticity problem (2.7) becomes: Find $(\boldsymbol{\sigma}, \mathbf{u}) \in \mathcal{H}$ such that

$$\mathbf{A}((\boldsymbol{\sigma}, \mathbf{u}), (\boldsymbol{\tau}, \mathbf{v})) = \mathbf{F}(\boldsymbol{\tau}, \mathbf{v}) \quad \forall \ (\boldsymbol{\tau}, \mathbf{v}) \in \mathcal{H},$$
(2.10)

where the form $\mathbf{A}: \mathcal{H} \times \mathcal{H} \to \mathbb{R}$ and the functional $\mathbf{F}: \mathcal{H} \to \mathbb{R}$ are given by

$$\mathbf{A}((\boldsymbol{\sigma}, \mathbf{u}), (\boldsymbol{\tau}, \mathbf{v})) := \int_{\Omega} \mathscr{C}^{-1} \boldsymbol{\sigma} : \boldsymbol{\tau} + \int_{\Omega} \boldsymbol{\omega}(\mathbf{u}) : \boldsymbol{\tau} + \int_{\Omega} \mathbf{u} \cdot \mathbf{div} \, \boldsymbol{\tau} - \int_{\Omega} \boldsymbol{\omega}(\mathbf{v}) : \boldsymbol{\sigma} - \int_{\Omega} \mathbf{v} \cdot \mathbf{div} \, \boldsymbol{\sigma} \\ + \kappa_1 \int_{\Omega} \left\{ \mathbf{e}(\mathbf{u}) - \mathscr{C}^{-1} \boldsymbol{\sigma} \right\} : \left\{ \mathbf{e}(\mathbf{v}) + \mathscr{C}^{-1} \boldsymbol{\tau} \right\} + \kappa_2 \int_{\Omega} \mathbf{div} \, \boldsymbol{\sigma} \cdot \mathbf{div} \, \boldsymbol{\tau} + \kappa_3 \int_{\Gamma} \mathbf{u} \cdot \mathbf{v}, \quad (2.11)$$

and

$$\mathbf{F}(\boldsymbol{\tau}, \mathbf{v}) = \int_{\Omega} \mathbf{f} \cdot \left\{ \mathbf{v} - \kappa_2 \mathbf{div} \,\boldsymbol{\tau} \right\} + \kappa_1 \left(\frac{1}{3|\Omega|} \int_{\Gamma} \mathbf{u}_D \cdot \boldsymbol{\nu} \right) \int_{\Gamma} \mathbf{v} \cdot \boldsymbol{\nu} + \langle \,\boldsymbol{\tau} \boldsymbol{\nu}, \mathbf{u}_D \,\rangle_{\Gamma} + \kappa_3 \int_{\Gamma} \mathbf{u}_D \cdot \mathbf{v}, \quad (2.12)$$

for all $(\sigma, \mathbf{u}), (\tau, \mathbf{v}) \in \mathcal{H}$. In what follows we see that the augmentation plays a key role in this formulation. More precisely, we now define the norm in \mathcal{H} as

$$\|(\boldsymbol{\tau}, \mathbf{v})\|_{\mathcal{H}} := \left\{ \|\boldsymbol{\tau}\|_{\mathbf{div},\Omega}^2 + \|\mathbf{v}\|_{1,\Omega}^2 \right\}^{1/2},$$

and establish the coercivity of A by considering suitable ranges for the stabilization parameters.

Lemma 2.2. Assume that $\kappa_1 \in (0, 2\mu)$ and $\kappa_2, \kappa_3 \in (0, \infty)$. Then, there exists $\alpha(\Omega) > 0$ independent of λ , such that

$$\mathbf{A}((\boldsymbol{\tau}, \mathbf{v}), (\boldsymbol{\tau}, \mathbf{v})) \ge \alpha(\Omega) \| (\boldsymbol{\tau}, \mathbf{v}) \|_{\mathcal{H}}^2 \quad \forall \ (\boldsymbol{\tau}, \mathbf{v}) \in \mathcal{H}.$$
(2.13)

Proof. First, we rewrite the first term that defines \mathbf{A} (cf. (2.11)) as

$$\int_{\Omega} \mathscr{C}^{-1} \boldsymbol{\sigma} : \boldsymbol{\tau} = \frac{1}{2\mu} \int_{\Omega} \boldsymbol{\sigma}^{\mathsf{d}} : \boldsymbol{\tau}^{\mathsf{d}} + \frac{1}{3(2\mu + 3\lambda)} \int_{\Omega} \operatorname{tr}(\boldsymbol{\sigma}) \operatorname{tr}(\boldsymbol{\tau}).$$

Then, for any $(\boldsymbol{\tau}, \mathbf{v}) \in \mathcal{H}$, we see that

$$\mathbf{A}((\boldsymbol{\tau}, \mathbf{v}), (\boldsymbol{\tau}, \mathbf{v})) = \int_{\Omega} \mathscr{C}^{-1} \boldsymbol{\tau} : \boldsymbol{\tau} - \kappa_1 \| \mathscr{C}^{-1} \boldsymbol{\tau} \|_{0,\Omega}^2 + \kappa_1 \| \mathbf{e}(\mathbf{v}) \|_{0,\Omega}^2 + \kappa_2 \| \operatorname{div} \boldsymbol{\tau} \|_{0,\Omega}^2 + \kappa_3 \| \mathbf{v} \|_{0,\Gamma}^2$$

$$= \frac{1}{2\mu} \left(1 - \frac{\kappa_1}{2\mu} \right) \| \boldsymbol{\tau}^{\mathsf{d}} \|_{0,\Omega}^2 + \frac{1}{3(2\mu + 3\lambda)} \left(1 - \frac{\kappa_1}{2\mu + 3\lambda} \right) \| \operatorname{tr}(\boldsymbol{\tau}) \|_{0,\Omega}^2$$

$$+ \kappa_1 \| \mathbf{e}(\mathbf{v}) \|_{0,\Omega}^2 + \kappa_2 \| \operatorname{div} \boldsymbol{\tau} \|_{0,\Omega}^2 + \kappa_3 \| \mathbf{v} \|_{0,\Gamma}^2.$$
(2.14)

Notice that, if $\kappa_1 < 2\mu$, then not only $1 - \frac{\kappa_1}{2\mu} > 0$ but also $1 - \frac{\kappa_1}{2\mu+3\lambda} > 0$. Therefore, discarding the term with $\|\operatorname{tr}(\boldsymbol{\tau})\|_{0,\Omega}^2$, and using Lemma 2.1, there holds for any $(\boldsymbol{\tau}, \mathbf{v}) \in \mathcal{H}$ that

$$\mathbf{A}((\boldsymbol{\tau}, \mathbf{v}), (\boldsymbol{\tau}, \mathbf{v})) \geq \alpha_1 c_1 \| \boldsymbol{\tau} \|_{0,\Omega}^2 + \frac{\kappa_2}{2} \| \operatorname{\mathbf{div}} \boldsymbol{\tau} \|_{0,\Omega}^2 + \alpha_2 c_3 \| \mathbf{v} \|_{1,\Omega}^2,$$

where

$$\alpha_1 := \min\left\{\frac{1}{2\mu}\left(1 - \frac{\kappa_1}{2\mu}\right), \frac{\kappa_2}{2}\right\} \text{ and } \alpha_2 := \min\{\kappa_1, \kappa_3\}.$$

In this way, denoting by

$$\alpha_3 := \min\left\{\alpha_1 c_1, \frac{\kappa_2}{2}\right\}$$

there exists $\alpha(\Omega) := \min\{\alpha_3, \alpha_2 c_3\}$, clearly independent of λ , such that (2.13) holds.

For computational purposes, and based on the proof of the previous Lemma, we can use the following stabilization parameters to make α as large as possible: $\kappa_1 = \mu$, $\kappa_2 = \frac{1}{2\mu}$ and $\kappa_3 = \kappa_1 = \mu$. Thus, the Lax-Milgram theorem (see, e.g., [12, Theorem 1.1]) provides the well-posedness result for (2.10) in similar terms as [13, Theorem 3.2].

Theorem 2.3. Under the assumptions of Lemma 2.2, there exists a unique $(\sigma, \mathbf{u}) \in \mathcal{H}$ solution to the weak formulation (2.10). Moreover, there exists C > 0, independent of λ , such that

$$\|(\boldsymbol{\sigma}, \mathbf{u})\|_{\mathcal{H}} \leq \frac{\|\mathbf{F}\|}{\alpha(\Omega)} \leq C \Big\{ \|\mathbf{f}\|_{0,\Omega} + \|\mathbf{u}_D\|_{1/2,\Gamma} \Big\}.$$
(2.15)

Proof. We remark that $\|\mathbf{e}(\mathbf{v})\|_{0,\Omega}, \|\boldsymbol{\omega}(\mathbf{v})\|_{0,\Omega} \leq \|\mathbf{v}\|_{1,\Omega}$ for any $\mathbf{v} \in \mathbf{H}^1(\Omega)$, and therefore, it is straightforward from [13, Theorem 3.1] that \mathbf{A} is a bilinear and bounded form in $\mathcal{H} \times \mathcal{H}$, since it is a reduced version of the one considered there as no vorticity-related terms have been added. On the other hand, it is clear that the term in brackets at the right hand side of (2.15) is nothing but a bound for $\|\mathbf{F}\|$. Therefore, Lemma 2.2 and the foregoing arguments satisfy the hypotheses of the Lax-Milgram theorem, thus getting existence and uniqueness for (2.10).

2.2 Boussinesq problem with nonconstant physical properties

Any reduction in the computational cost of a numerical method is valuable, but perhaps it is more desirable when a high number of variables and degrees of freedom is inevitable, as in the case of fully-mixed methods for coupled problems in three dimensions. Indeed, we now consider the flow of a non-isothermal, incompressible, Newtonian fluid with varying viscosity within a region Ω . Then, a model for this phenomenon is given by a generalized version of the Boussinesq equations, that when considered in the form [1], and neglecting the definition of the vorticity, seeks a rate of strain \mathbf{t} , a pseudostress $\boldsymbol{\sigma}$, a velocity \mathbf{u} , a temperature gradient (o diffusive heat flux) $\boldsymbol{\zeta}$, a total heat flux \mathbf{p} , and a temperature φ such that

$$-\nabla \mathbf{u} + \mathbf{t} + \boldsymbol{\omega}(\mathbf{u}) = \mathbf{0} \quad \text{in } \Omega, \qquad \mu(\varphi)\mathbf{t} - (\mathbf{u} \otimes \mathbf{u})^{\mathbf{d}} - \boldsymbol{\sigma}^{\mathbf{d}} = \mathbf{0} \quad \text{in } \Omega,$$

$$-\mathbf{div} \,\boldsymbol{\sigma} - \varphi \mathbf{g} = \mathbf{f}^{\mathbf{m}} \quad \text{in } \Omega, \qquad \mathbf{u} = \mathbf{0} \quad \text{on } \Gamma, \qquad \int_{\Omega} \operatorname{tr}(\boldsymbol{\sigma} + \mathbf{u} \otimes \mathbf{u}) = 0,$$

$$-\nabla \varphi + \boldsymbol{\zeta} = \mathbf{0} \quad \text{in } \Omega, \qquad \mathbf{p} = k(\varphi)\boldsymbol{\zeta} - \varphi \mathbf{u} \quad \text{in } \Omega,$$

$$-\operatorname{div} \mathbf{p} = f^{\mathbf{e}} \quad \text{in } \Omega, \qquad \varphi = \varphi_{D} \quad \text{on } \Gamma_{D}, \qquad \mathbf{p} \cdot \boldsymbol{\nu} = 0 \quad \text{on } \Gamma_{N},$$

$$(2.16)$$

where the boundary $\partial \Omega =: \Gamma$ has been split as $\Gamma = \Gamma_D \cup \Gamma_N$ with $\Gamma_D \cap \Gamma_N = \emptyset$, $-\mathbf{g} \in \mathbf{L}^{\infty}(\Omega)$ is a body force, $\mathbf{f}^{\mathbf{m}} \in \mathbf{L}^2(\Omega)$ and $f^{\mathbf{e}} \in \mathbf{L}^2(\Omega)$ are source terms, and $\varphi_D \in \mathrm{H}^{1/2}(\Gamma_D)$ is a prescribed temperature on part of the boundary. Furthermore, $\mu, k : \mathbb{R} \to \mathbb{R}^+$ are temperature-dependent viscosity and thermal conductivity functions, respectively, which are assumed to be bounded and Lipschitz continuous, that is, there exists $\mu_2 \ge \mu_1 > 0$, $L_{\mu} > 0$, $k_2 \ge k_1 > 0$, $L_k > 0$ such that for any $s, t \in \mathbb{R}$

$$\mu_1 \le \mu(t) \le \mu_2, \qquad |\mu(s) - \mu(t)| \le L_\mu |s - t|$$
(2.17)

and

$$k_1 \le k(t) \le k_2, \qquad |k(s) - k(t)| \le L_k |s - t|.$$
 (2.18)

On the one hand, recalling that $\mathbf{t} = \mathbf{e}(\mathbf{u})$ is a symmetric, null-trace tensor (the fluid is incompressible), we take into consideration the space:

$$\mathbb{L}^{2}_{\mathtt{tr}}(\Omega) := \Big\{ \mathbf{s} \in \mathbb{L}^{2}(\Omega) : \mathbf{s} = \mathbf{s}^{\mathtt{t}} \text{ and } \mathrm{tr}(\mathbf{s}) = 0 \Big\}.$$

On the other hand, the Neumann condition for the total heat flux leads us to consider for this variable the space:

$$\mathbf{H}_{\mathrm{N}}(\mathrm{div};\Omega) := \left\{ \mathbf{q} \in \mathbf{H}(\mathrm{div};\Omega) : \quad \mathbf{q} \cdot \boldsymbol{\nu} = 0 \quad \mathrm{on} \ \Gamma_{N} \right\}.$$

In this way, integrating by parts the first and sixth equation of (2.16) and properly testing the remaining equations (see [1, Section 3.1] for more details), a fully-mixed weak formulation for (2.16) with ultra-weak symmetry is given by: Find $(\mathbf{t}, \boldsymbol{\sigma}, \mathbf{u}, \boldsymbol{\zeta}, \mathbf{p}, \varphi) \in \mathbb{L}^2_{tr}(\Omega) \times \mathbb{H}_0(\mathbf{div}; \Omega) \times \mathbf{H}^1(\Omega) \times \mathbf{L}^2(\Omega) \times \mathbf{H}_N(\mathbf{div}; \Omega) \times \mathbf{H}^1(\Omega)$ such that

$$\int_{\Omega} \mu(\varphi) \mathbf{t} : \mathbf{s} - \int_{\Omega} (\mathbf{u} \otimes \mathbf{u})^{\mathbf{d}} : \mathbf{s} - \int_{\Omega} \boldsymbol{\sigma}^{\mathbf{d}} : \mathbf{s} = 0 \qquad \forall \mathbf{s} \in \mathbb{L}^{2}_{tr}(\Omega),$$

$$\int_{\Omega} \mathbf{t} : \boldsymbol{\tau}^{\mathbf{d}} + \int_{\Omega} \boldsymbol{\omega}(\mathbf{u}) : \boldsymbol{\tau} + \int_{\Omega} \mathbf{u} \cdot \mathbf{div} \, \boldsymbol{\tau} = 0 \qquad \forall \mathbf{\tau} \in \mathbb{H}_{0}(\mathbf{div};\Omega),$$

$$- \int_{\Omega} \boldsymbol{\omega}(\mathbf{v}) : \boldsymbol{\sigma} - \int_{\Omega} \mathbf{v} \cdot \mathbf{div} \, \boldsymbol{\sigma} = \int_{\Omega} \left\{ \varphi \mathbf{g} + \mathbf{f}^{\mathbf{m}} \right\} \cdot \mathbf{v} \qquad \forall \mathbf{v} \in \mathbf{H}^{1}_{0}(\Omega),$$

$$\int_{\Omega} k(\varphi) \, \boldsymbol{\zeta} \cdot \boldsymbol{\chi} - \int_{\Omega} \varphi \mathbf{u} \cdot \boldsymbol{\chi} - \int_{\Omega} \mathbf{p} \cdot \boldsymbol{\chi} = 0 \qquad \forall \boldsymbol{\chi} \in \mathbf{L}^{2}(\Omega),$$

$$\int_{\Omega} \boldsymbol{\zeta} \cdot \mathbf{q} + \int_{\Omega} \varphi \operatorname{div} \mathbf{q} = \langle \mathbf{q} \cdot \boldsymbol{\nu}, \varphi_{D} \rangle_{\Gamma_{D}} \qquad \forall \mathbf{q} \in \mathbf{H}_{N}(\operatorname{div};\Omega),$$

$$- \int_{\Omega} \psi \operatorname{div} \mathbf{p} = \int_{\Omega} f^{\mathbf{e}} \psi \qquad \forall \psi \in \mathbf{H}^{1}(\Omega).$$
(2.19)

Notice that the ultra-weak imposition of the symmetry of the pseudostress tensor has been included as the first term in the third equation of (2.19). Then, we proceed to augment this formulation with the following terms:

$$\begin{split} \kappa_1 \int_{\Omega} \left\{ \boldsymbol{\sigma}^{\mathbf{d}} + (\mathbf{u} \otimes \mathbf{u})^{\mathbf{d}} - \boldsymbol{\mu}(\varphi) \mathbf{t} \right\} : \boldsymbol{\tau}^{\mathbf{d}} &= 0 & \forall \ \boldsymbol{\tau} \in \mathbb{H}_0(\mathbf{div}; \Omega), \\ \kappa_2 \int_{\Omega} \mathbf{div} \ \boldsymbol{\sigma} \cdot \mathbf{div} \ \boldsymbol{\tau} &= -\kappa_2 \int_{\Omega} \left\{ \varphi \mathbf{g} + \mathbf{f}^{\mathbf{m}} \right\} \cdot \mathbf{div} \ \boldsymbol{\tau} & \forall \ \boldsymbol{\tau} \in \mathbb{H}_0(\mathbf{div}; \Omega), \\ \kappa_3 \int_{\Omega} \left\{ \mathbf{e}(\mathbf{u}) - \mathbf{t} \right\} : \mathbf{e}(\mathbf{v}) &= 0 & \forall \ \mathbf{v} \in \mathbf{H}_0^1(\Omega), \\ \kappa_4 \int_{\Omega} \left\{ \mathbf{p} + \varphi \mathbf{u} - k(\varphi) \boldsymbol{\zeta} \right\} \cdot \mathbf{q} &= 0 & \forall \ \mathbf{q} \in \mathbf{H}_N(\mathbf{div}; \Omega), \\ \kappa_5 \int_{\Omega} \mathbf{div} \ \mathbf{p} \ \mathbf{div} \ \mathbf{q} &= -\kappa_5 \int_{\Omega} f^{\mathbf{e}} \ \mathbf{div} \ \mathbf{q} & \forall \ \mathbf{q} \in \mathbf{H}_N(\mathbf{div}; \Omega), \\ \kappa_6 \int_{\Omega} \left\{ \nabla \varphi - \boldsymbol{\zeta} \right\} \cdot \nabla \psi &= 0 & \forall \ \psi \in \mathbf{H}^1(\Omega), \\ \kappa_7 \int_{\Gamma_D} \varphi \ \psi &= \kappa_7 \int_{\Gamma_D} \varphi_D \ \psi & \forall \ \psi \in \mathbf{H}^1(\Omega) \,. \end{split}$$

Next, denoting by

$$\begin{split} \mathcal{H} &:= \mathbb{L}^2_{\mathrm{tr}}(\times) \mathbb{H}_0(\mathrm{div};\Omega) \times \mathbf{H}^1(\Omega), \quad \mathcal{Q} := \mathbf{L}^2(\Omega) \times \mathbf{H}_N(\mathrm{div};\Omega) \times \mathrm{H}^1(\Omega), \\ \vec{\mathbf{t}} := (\mathbf{t}, \boldsymbol{\sigma}, \mathbf{u}), \quad \vec{\mathbf{s}} := (\mathbf{s}, \boldsymbol{\tau}, \mathbf{v}), \quad \vec{\boldsymbol{\zeta}} := (\boldsymbol{\zeta}, \mathbf{p}, \varphi), \quad \vec{\boldsymbol{\chi}} := (\boldsymbol{\chi}, \mathbf{q}, \psi), \end{split}$$

the augmented fully-mixed formulation of (2.16) is: Find $(\vec{t}, \vec{\zeta}) \in \mathcal{H} \times \mathcal{Q}$ such that

$$\mathbf{A}_{\varphi}(\vec{\mathbf{t}}, \vec{\mathbf{s}}) + \mathbf{B}_{\mathbf{u}}(\vec{\mathbf{t}}, \vec{\mathbf{s}}) = F_{\varphi}(\vec{\mathbf{s}}) + F_{\mathbb{m}}(\vec{\mathbf{s}}) \qquad \forall \ \vec{\mathbf{s}} \in \mathcal{H}, \\
\mathbf{C}_{\varphi}(\vec{\zeta}, \vec{\chi}) + \mathbf{D}_{\mathbf{u}}(\vec{\zeta}, \vec{\chi}) = G_D(\vec{\chi}) + G_{\mathsf{e}}(\vec{\chi}) \qquad \forall \ \vec{\chi} \in \mathcal{Q},$$
(2.20)

where, given $(\mathbf{w}, \phi) \in \mathbf{H}^1(\Omega) \times \mathrm{H}^1(\Omega)$, the bilinear forms \mathbf{A}_{ϕ} , $\mathbf{B}_{\mathbf{w}}$, \mathbf{C}_{ϕ} , $\mathbf{D}_{\mathbf{w}}$ and the linear functionals F_{ϕ} , $F_{\mathbb{m}}$, G_D and $G_{\mathbf{e}}$ are defined as:

$$\mathbf{A}_{\phi}(\vec{\mathbf{t}},\vec{\mathbf{s}}) = \int_{\Omega} \mu(\phi)\mathbf{t} : \{\mathbf{s} - \kappa_{1}\boldsymbol{\tau}^{d}\} + \int_{\Omega} \mathbf{t} : \{\boldsymbol{\tau}^{d} - \kappa_{3}\mathbf{e}(\mathbf{v})\} - \int_{\Omega}\boldsymbol{\sigma}^{d} : \{\mathbf{s} - \kappa_{1}\boldsymbol{\tau}^{d}\} + \int_{\Omega} \mathbf{u} \cdot \mathbf{div}\,\boldsymbol{\tau} + \int_{\omega} \boldsymbol{\omega}(\mathbf{u}) : \boldsymbol{\tau} - \int_{\Omega} \mathbf{v} \cdot \mathbf{div}\,\boldsymbol{\sigma} - \int_{\Omega} \boldsymbol{\omega}(\mathbf{v}) : \boldsymbol{\sigma} + \kappa_{2} \int_{\Omega} \mathbf{div}\,\boldsymbol{\sigma} \cdot \mathbf{div}\,\boldsymbol{\tau} + \kappa_{3} \int_{\Omega} \mathbf{e}(\mathbf{u}) : \mathbf{e}(\mathbf{v}),$$

$$(2.21)$$

$$\mathbf{B}_{\mathbf{w}}(\vec{\mathbf{t}},\vec{\mathbf{s}}) := -\int_{\Omega} (\mathbf{u} \otimes \mathbf{w})^{\mathbf{d}} : \{\mathbf{s} - \kappa_1 \boldsymbol{\tau}^{\mathbf{d}}\}, \qquad (2.22)$$

for all $\vec{t}, \vec{s} \in \mathcal{H};$

$$\mathbf{C}_{\phi}(\vec{\boldsymbol{\zeta}},\vec{\boldsymbol{\chi}}) := \int_{\Omega} k(\phi)\boldsymbol{\zeta} \cdot \{\boldsymbol{\chi} - \kappa_{4}\mathbf{q}\} + \int_{\Omega} \boldsymbol{\zeta} \cdot \{\mathbf{q} - \kappa_{6}\nabla\psi\} - \int_{\Omega} \mathbf{p} \cdot \{\boldsymbol{\chi} - \kappa_{4}\mathbf{q}\} + \int_{\Omega} \varphi \operatorname{div} \mathbf{q} - \int_{\Omega} \psi \operatorname{div} \mathbf{p} + \kappa_{5} \int_{\Omega} \operatorname{div} \mathbf{p} \operatorname{div} \mathbf{q} + \kappa_{6} \int_{\Omega} \nabla\varphi \cdot \nabla\psi + \kappa_{7} \int_{\Gamma_{D}} \varphi \psi, \qquad (2.23)$$

$$\mathbf{D}_{\mathbf{w}}(\vec{\boldsymbol{\zeta}}, \vec{\boldsymbol{\chi}}) := -\int_{\Omega} \varphi \mathbf{w} \cdot \{ \boldsymbol{\chi} - \kappa_4 \mathbf{q} \}, \qquad (2.24)$$

for all $\vec{\zeta}, \vec{\chi} \in \mathcal{Q};$

$$F_{\phi}(\vec{\mathbf{s}}) := \int_{\Omega} \phi \mathbf{g} \cdot \{ \mathbf{v} - \kappa_2 \mathbf{div} \, \boldsymbol{\tau} \}, \qquad (2.25)$$

$$F_{\mathbf{m}}(\vec{\mathbf{s}}) := \int_{\Omega} \mathbf{f}^{\mathbf{m}} \cdot \{ \mathbf{v} - \kappa_2 \mathbf{div} \, \boldsymbol{\tau} \}, \qquad (2.26)$$

for all $\vec{s} \in \mathcal{H}$;

$$G_D(\vec{\boldsymbol{\chi}}) := \langle \, \mathbf{q} \cdot \boldsymbol{\nu}, \varphi_D \, \rangle_{\Gamma_D} + \kappa_7 \int_{\Gamma_D} \varphi_D \, \psi, \qquad (2.27)$$

$$G_{\mathbf{e}}(\vec{\boldsymbol{\chi}}) := \int_{\Omega} f^{\mathbf{e}} \left\{ \psi - \kappa_5 \operatorname{div} \mathbf{q} \right\},$$
(2.28)

for all $\vec{\chi} \in \mathcal{Q}$. Now, we decouple (2.16) following [1, Section 3.2] (see, also [4], [7], [8]), and rewrite it as a fixed-point problem. Indeed, we denote $\mathbf{H} := \mathbf{H}^1(\Omega) \times \mathrm{H}^1(\Omega)$ and consider first the operator $\mathbf{M} : \mathbf{H} \to \mathcal{H}$ defined as

$$\mathbf{M}(\mathbf{w},\phi) = \left(\mathbf{M}_1(\mathbf{w},\phi), \mathbf{M}_2(\mathbf{w},\phi), \mathbf{M}_3(\mathbf{w},\phi)\right) := \vec{\mathbf{t}},$$

where $\vec{t} \in \mathcal{H}$ is the solution to:

$$\mathbf{A}_{\phi}(\vec{\mathbf{t}},\vec{\mathbf{s}}) + \mathbf{B}_{\mathbf{w}}(\vec{\mathbf{t}},\vec{\mathbf{s}}) = F_{\phi}(\vec{\mathbf{s}}) + F_{\mathtt{m}}(\vec{\mathbf{s}}) \quad \forall \ \vec{\mathbf{s}} \in \mathcal{H}.$$
(2.29)

Then, consider the operator $\mathbf{E}:\mathbf{H}\rightarrow\mathcal{Q}$ defined as

$$\mathbf{E}(\mathbf{w},\phi) = \left(\mathbf{E}_1(\mathbf{w},\phi), \mathbf{E}_2(\mathbf{w},\phi), \mathbf{E}_3(\mathbf{w},\phi)\right) := \vec{\boldsymbol{\zeta}},$$

where $\vec{\zeta} \in \mathcal{Q}$ is now the solution to:

$$\mathbf{C}_{\phi}(\vec{\boldsymbol{\zeta}},\vec{\boldsymbol{\chi}}) + \mathbf{D}_{\mathbf{w}}(\vec{\boldsymbol{\zeta}},\vec{\boldsymbol{\chi}}) = G_D(\vec{\boldsymbol{\chi}}) + G_{\mathsf{e}}(\vec{\boldsymbol{\chi}}) \quad \forall \; \vec{\boldsymbol{\chi}} \in \mathcal{Q}.$$
(2.30)

Consequently, we can define the operator $\mathbf{T}: \mathbf{H} \to \mathbf{H}$ as

$$\mathbf{T}(\mathbf{w},\phi) := \Big(\mathbf{M}_3(\mathbf{w},\phi), \mathbf{E}_3(\mathbf{M}_3(\mathbf{w},\phi),\phi)\Big),\tag{2.31}$$

and transform (2.20) into the problem: Find $(\mathbf{u}, \varphi) \in \mathbf{H}$ such that

$$\mathbf{T}(\mathbf{u},\varphi) = (\mathbf{u},\varphi). \tag{2.32}$$

Again, the similarity of $\mathbf{A}_{\phi} + \mathbf{B}_{\mathbf{w}}$ with respect to the one defined in [1] leads us to only analyze its coercivity to conclude that (2.32) is a well-posed problem.

Lemma 2.4. Assume that for $\delta_1 \in \left(0, \frac{2}{\mu_2}\right)$ and $\delta_2 \in (0, 2)$ we choose

$$\kappa_1 \in \left(0, \frac{2\delta_1\mu_1}{\mu_2}\right), \quad \kappa_2 \in (0, \infty) \quad and \quad \kappa_3 \in \left(0, 2\delta_2\left(\mu_1 - \frac{\kappa_1\mu_2}{2\delta_1}\right)\right).$$

Then, there exists $r_1 > 0$ such that for each $r \in (0, r_1)$, the bilinear form $\mathbf{A}_{\phi} + \mathbf{B}_{\mathbf{w}}$ is strongly coercive in \mathcal{H} for each $(\mathbf{w}, \phi) \in \mathbf{H}$ such that $\|\mathbf{w}\|_{1,\Omega} \leq r$. More precisely, there exists $\alpha(\Omega) > 0$ such that

$$(\mathbf{A}_{\phi} + \mathbf{B}_{\mathbf{w}})(\vec{\mathbf{s}}, \vec{\mathbf{s}}) \ge \frac{\alpha(\Omega)}{2} \| \vec{\mathbf{s}} \|^2 \quad \forall \vec{\mathbf{s}} \in \mathcal{H}.$$
(2.33)

Proof. Let $(\mathbf{w}, \phi) \in \mathbf{H}$ and $\mathbf{\vec{s}} \in \mathcal{H}$. Then, from (2.21) we see that for \mathbf{A}_{ϕ} there holds

$$\begin{split} \mathbf{A}_{\phi}(\vec{\mathbf{s}},\vec{\mathbf{s}}) &= \int_{\Omega} \mu(\phi) \mathbf{s} : \mathbf{s} - \kappa_1 \int_{\Omega} \mu(\phi) \mathbf{s} : \boldsymbol{\tau}^{\mathbf{d}} - \kappa_3 \int_{\Omega} \mathbf{s} : \mathbf{e}(\mathbf{v}) \\ &+ \kappa_1 \left\| \boldsymbol{\tau}^{\mathbf{d}} \right\|_{0,\Omega}^2 + \kappa_2 \| \operatorname{\mathbf{div}} \boldsymbol{\tau} \|_{0,\Omega}^2 + \kappa_3 \| \mathbf{e}(\mathbf{v}) \|_{0,\Omega}^2. \end{split}$$

Then, using the bounds of the viscosity function (2.17), the Cauchy-Schwarz and Young inequalities and Lemma 2.1, we obtain for any $\delta_1, \delta_2 > 0$ that

$$\begin{split} \mathbf{A}_{\phi}(\vec{\mathbf{s}},\vec{\mathbf{s}}) &\geq \left(\mu_{1} - \frac{\kappa_{1}\mu_{2}}{2\delta_{1}} - \frac{\kappa_{3}}{2\delta_{2}}\right) \|\mathbf{s}\|_{0,\Omega}^{2} + \kappa_{1}\left(1 - \frac{\mu_{2}\delta_{1}}{2}\right) \|\boldsymbol{\tau}^{\mathsf{d}}\|_{0,\Omega}^{2} \\ &+ \kappa_{2} \|\operatorname{\mathbf{div}}\boldsymbol{\tau}\|_{0,\Omega}^{2} + \kappa_{3}\left(1 - \frac{\delta_{2}}{2}\right) \|\mathbf{e}(\mathbf{v})\|_{0,\Omega}^{2}, \end{split}$$

and therefore, defining

$$\alpha_1 := \mu_1 - \frac{\kappa_1 \mu_2}{2\delta_1} - \frac{\kappa_3}{2\delta_2}, \quad \alpha_2 := \min\left\{\kappa_1 \left(1 - \frac{\mu_2 \delta_1}{2}\right), \frac{\kappa_2}{2}\right\},$$
$$\alpha_3 := \min\left\{\alpha_2 c_1, \frac{\kappa_2}{2}\right\}, \quad \alpha_4 := \kappa_3 \left(1 - \frac{\delta_2}{2}\right) c_2 c_P,$$

with $c_P > 0$ being the constant in Poincaré's inequality, and δ_1 , δ_2 restricted to the ranges indicated in the hypotheses, we find that there exists $\alpha(\Omega) := \min\{\alpha_1, \alpha_3, \alpha_4\}$ such that

$$\mathbf{A}_{\phi}(\vec{\mathbf{s}}, \vec{\mathbf{s}}) \geq \alpha(\Omega) \| \vec{\mathbf{s}} \|^2 \quad \forall \ \vec{\mathbf{s}} \in \mathcal{H}.$$

On the other hand, using the Cauchy-Schwarz inequality twice, and that $\mathbf{H}^{1}(\Omega)$ is continuously embedded into $\mathbf{L}^{4}(\Omega)$ with constant $c_{\mathbf{i}}(\Omega) > 0$, we deduce from (2.22) that

$$-\mathbf{B}_{\mathbf{w}}(\vec{\mathbf{s}},\vec{\mathbf{s}}) \le c_{\mathbf{i}}^2 (1+\kappa_1^2)^{1/2} \|\mathbf{w}\|_{1,\Omega} \|\vec{\mathbf{s}}\|^2.$$

In this way, putting together the last two equations, we obtain

$$(\mathbf{A}_{\phi} + \mathbf{B}_{\mathbf{w}})(\vec{\mathbf{s}}, \vec{\mathbf{s}}) \ge \left(\alpha(\Omega) - c_{\mathbf{i}}^2 (1 + \kappa_1^2)^{1/2} \| \mathbf{w} \|_{1,\Omega}\right) \| \vec{\mathbf{s}} \|^2$$

and therefore

$$(\mathbf{A}_{\phi} + \mathbf{B}_{\mathbf{w}})(\vec{\mathbf{s}}, \vec{\mathbf{s}}) \ge \frac{\alpha(\Omega)}{2} \|\vec{\mathbf{s}}\|^2,$$

provided that

$$\|\mathbf{w}\|_{1,\Omega} \le \frac{\alpha(\Omega)}{2c_{\mathbf{i}}^2(1+\kappa_1^2)^{1/2}} =: r_1.$$

In turn, as the mixed formulation (2.30) of the energy equation has not changed with respect to the one in [1], we recall the coercivity result for $\mathbf{C}_{\phi} + \mathbf{D}_{\mathbf{w}}$ from [1, Lemma 3.3].

Lemma 2.5. Assume that for $\delta_3 \in \left(0, \frac{2}{k_2}\right)$, $\delta_4 \in (0, 2)$ we choose

$$\kappa_4 \in \left(0, \frac{2\delta_3 k_1}{k_2}\right), \quad \kappa_5, \kappa_7 \in (0, \infty) \quad and \quad \kappa_6 \in \left(0, 2\delta_4 \left(k_1 - \frac{\kappa_4 k_2}{2\delta_3}\right)\right).$$

Then, there exists $r_2 > 0$ such that for each $r \in (0, r_2)$, the bilinear form $\mathbf{C}_{\phi} + \mathbf{D}_{\mathbf{w}}$ is strongly coercive in \mathcal{Q} for each $(\mathbf{w}, \phi) \in \mathbf{H}$ such that $\|\mathbf{w}\|_{1,\Omega}^2 \leq r$. More precisely, there exists $\beta(\Omega) > 0$ such that

$$(\mathbf{C}_{\phi} + \mathbf{D}_{\mathbf{w}})(\vec{\boldsymbol{\chi}}, \vec{\boldsymbol{\chi}}) \ge \frac{\beta(\Omega)}{2} \| \vec{\boldsymbol{\chi}} \|^2 \quad \forall \; \vec{\boldsymbol{\chi}} \in \mathcal{Q}.$$
(2.34)

In this way, for computational purposes, we choose δ_1 , δ_2 , κ_1 , κ_3 , δ_3 , δ_4 , κ_4 , and κ_6 as the midpoints of their respective ranges, and take the remaining parameters so as to maximize the computable constants defining $\alpha(\Omega)$ and $\beta(\Omega)$. In this way, we obtain

$$\kappa_1 = \frac{\mu_1}{\mu_2^2}, \quad \kappa_2 = \frac{\mu_1}{\mu_2^2} \quad \kappa_3 = \frac{\mu_1}{2}, \quad \kappa_4 = \frac{k_1}{k_2^2},$$

 $\kappa_5 = \frac{k_1}{2\kappa_2^2}, \quad \kappa_6 = \frac{k_1}{2}, \quad \kappa_7 = \frac{k_1}{4}.$

Consequently, under the assumptions of Lemmas 2.4 and 2.5, both (2.29) and (2.30) are well-posed problems by means of the Lax-Milgram theorem, and therefore, the operator \mathbf{T} given by (2.31) is well-defined in similar terms as [1, Lemma 3.4]. Then, the analysis of the fixed-point problem can be carried out in the exact same terms as [1, Section 3.4], since we are again benefited by the fact that vorticity does not play a role in these results, and moreover, the aforementioned operators \mathbf{M} and \mathbf{E} coincide with the ones presented in [1]. This leads to (2.32) being a well-posed problem thanks to the Banach fixed-point theorem under some smallness-of-data and suitable regularity assumptions that are not worth mentioning again, for the sake of briefness of this paper. We refer to [1, Theorem 3.9] for further details.

3 Mixed finite element methods

We first present the Galerkin schemes for (2.10) and (2.20) and then specify finite element spaces, based on the flexibility that augmented methods provide. For now, let us consider arbitrary finite dimensional subspaces $\mathbb{H}_{h}^{t} \subset \mathbb{L}_{tr}^{2}(\Omega)$, $\mathbb{H}_{h}^{\sigma} \subset \mathbb{H}_{0}(\operatorname{div}; \Omega)$, $\mathbf{H}_{h}^{u} \subset \mathbf{H}^{1}(\Omega)$, $\mathbf{H}_{h}^{\zeta} \subset \mathbf{L}^{2}(\Omega)$, $\mathbf{H}_{h}^{\mathbf{p}} \subset \mathbf{H}_{N}(\operatorname{div}; \Omega)$ and $\mathbf{H}_{h}^{\varphi} \subset \mathbf{H}^{1}(\Omega)$, as well as \mathcal{T}_{h} be a regular triangulation of $\overline{\Omega}$ made by tetrahedrons T (when $\Omega \subset \mathbb{R}^{3}$) or triangles T (when $\Omega \subset \mathbb{R}^{2}$) of diameter h_{T} and define the meshsize $h := \max\{h_{T}: T \in \mathcal{T}_{h}\}$.

3.1 Linear elasticity

Regarding (2.10), the Galerkin scheme reads: Find $(\boldsymbol{\sigma}_h, \mathbf{u}_h) \in \mathbb{H}_h^{\boldsymbol{\sigma}} \times \mathbf{H}_h^{\mathbf{u}}$ such that

$$\mathbf{A}((\boldsymbol{\sigma}_h, \mathbf{u}_h), (\boldsymbol{\tau}_h, \mathbf{v}_h)) = \mathbf{F}(\boldsymbol{\tau}_h, \mathbf{v}_h) \quad \forall \ (\boldsymbol{\tau}_h, \mathbf{v}_h) \in \mathbb{H}_h^{\boldsymbol{\sigma}} \times \mathbf{H}_h^{\mathbf{u}},$$
(3.1)

with **A** and **F** defined respectively as in (2.11) and (2.12). Following [13], by using the same values for the stabilization parameters as in Lemma 2.2, and since the bilinear form **A** is strongly-coercive in $\mathbb{H}_0(\operatorname{div}; \Omega) \times \mathbf{H}^1(\Omega)$ (and so it is in $\mathbb{H}_h^{\sigma} \times \mathbf{H}_h^{\mathbf{u}}$), the variational formulation (3.1) is well-posed. Moreover, there exists positive constants C and \widetilde{C} , independent of λ and h such that

$$\| (\boldsymbol{\sigma}_h, \mathbf{u}_h) \|_{\mathcal{H}} \leq C \Big\{ \| \mathbf{f} \|_{0,\Omega} + \| \mathbf{g} \|_{1/2,\Gamma} \Big\}$$

and

$$\|(\boldsymbol{\sigma}, \mathbf{u}) - (\boldsymbol{\sigma}_h, \mathbf{u}_h)\|_{\mathcal{H}} \leq \widetilde{C} \inf_{(\boldsymbol{\tau}_h, \mathbf{v}_h) \in \mathbb{H}_h^{\boldsymbol{\sigma}} \times \mathbf{H}_h^{\mathbf{u}}} \|(\boldsymbol{\sigma}, \mathbf{u}) - (\boldsymbol{\tau}_h, \mathbf{v}_h)\|.$$
(3.2)

3.2 Boussinesq problem with temperature-dependent viscosity

Now, considering (2.20) and denoting by

$$\mathcal{H}_h := \mathbb{H}_h^{\mathbf{t}} \times \mathbb{H}_h^{\boldsymbol{\sigma}} \times \mathbf{H}_h^{\mathbf{u}}, \quad \mathcal{Q}_h := \mathbf{H}_h^{\boldsymbol{\zeta}} \times \mathbf{H}_h^{\mathbf{p}} \times \mathbb{H}_h^{\varphi}$$
(3.3)

$$\vec{\mathbf{t}}_h := (\mathbf{t}_h, \boldsymbol{\sigma}_h, \mathbf{u}_h), \quad \vec{\mathbf{s}}_h := (\mathbf{s}_h, \boldsymbol{\tau}_h, \mathbf{v}_h), \quad \vec{\boldsymbol{\zeta}}_h := (\boldsymbol{\zeta}_h, \mathbf{p}_h, \varphi_h), \quad \vec{\boldsymbol{\chi}}_h := (\boldsymbol{\chi}_h, \mathbf{q}_h, \psi_h), \quad (3.4)$$

the Galerkin scheme for this problem is given by: Find $(\vec{t}_h, \vec{\zeta}_h) \in \mathcal{H}_h \times \mathcal{Q}_h$ such that

$$\mathbf{A}_{\varphi_{h}}(\vec{\mathbf{t}}_{h},\vec{\mathbf{s}}_{h}) + \mathbf{B}_{\mathbf{u}_{h}}(\vec{\mathbf{t}}_{h},\vec{\mathbf{s}}_{h}) = F_{\varphi_{h}}(\vec{\mathbf{s}}_{h}) + F_{\mathtt{m}}(\vec{\mathbf{s}}_{h}) \qquad \forall \ \vec{\mathbf{s}}_{h} \in \mathcal{H}_{h}, \\
\mathbf{C}_{\varphi_{h}}(\vec{\boldsymbol{\zeta}}_{h},\vec{\boldsymbol{\chi}}_{h}) + \mathbf{D}_{\mathbf{u}_{h}}(\vec{\boldsymbol{\zeta}}_{h},\vec{\boldsymbol{\chi}}_{h}) = G_{D}(\vec{\boldsymbol{\chi}}_{h}) + G_{\mathtt{e}}(\vec{\boldsymbol{\chi}}_{h}) \qquad \forall \ \vec{\boldsymbol{\chi}}_{h} \in \mathcal{Q}_{h},$$
(3.5)

where the forms \mathbf{A}_{φ_h} , $\mathbf{B}_{\mathbf{u}_h}$, \mathbf{C}_{φ_h} , $\mathbf{D}_{\mathbf{u}_h}$, and the functionals F_{φ_h} , $F_{\mathbf{m}}$, G_D , $G_{\mathbf{e}}$, are defined by (2.21)-(2.28). Following [1], existence of a solution to this problem is guaranteed primarily whenever the stabilization parameters are taken as in Lemmas 2.4 and 2.5 (in order to have strong coercivity) and smallness-of-data assumptions like the one presented in [1, Theorem 4.8] hold. In this way, it is possible to prove following [1, Section 4.2] that there exists positive constants $C_{\mathbf{M}}$, $C_{\mathbf{E}}$ such that

$$\left\| \vec{\mathbf{t}}_{h} \right\|_{\mathcal{H}} \leq C_{\mathbf{M}} \Big\{ r \| \mathbf{g} \|_{\infty,\Omega} + \| \mathbf{f}^{\mathtt{m}} \|_{0,\Omega} \Big\}$$

and

$$\|\vec{\boldsymbol{\zeta}}_h\|_{\boldsymbol{\mathcal{Q}}} \leq C_{\mathbf{E}}\Big\{\|\varphi_D\|_{1/2,\Gamma_D} + \|f^{\mathbf{e}}\|_{0,\Omega}\Big\}.$$

Regarding a Céa's estimate for this problem, while it can not be derived as simply as in the Linear Elasticity case, it follows the same scheme as in [1, Section 5]. Once again, vorticity does not play a role in the *a priori* error analysis, as the difference between continuous and discrete forms from

Strang's Lemma vanish all but nonlinear terms. Therefore, we conclude that, given data sufficiently small, there exists a constant $\tilde{C} > 0$ independent of h such that

$$\left\| \left(\vec{\mathbf{t}}, \vec{\boldsymbol{\zeta}} \right) - \left(\vec{\mathbf{t}}_h, \vec{\boldsymbol{\zeta}}_h \right) \right\| \le \widetilde{C} \left\{ \inf_{\vec{\mathbf{s}}_h \in \mathcal{H}_h} \left\| \vec{\mathbf{t}} - \vec{\mathbf{s}}_h \right\|_{\mathcal{H}} + \inf_{\vec{\boldsymbol{\chi}}_h \in \mathcal{Q}_h} \left\| \vec{\boldsymbol{\zeta}} - \vec{\boldsymbol{\chi}}_h \right\|_{\mathcal{Q}} \right\}.$$
(3.6)

3.3 Specification of finite element spaces

It is important to notice that eliminating the vorticity from the system has not imposed any additional restriction on the choice of finite elements, and hence the flexibility on this matter that characterize augmented methods has not been lost. Therefore, we consider these subspaces as in their original works ([13] and [1]), i.e., given an integer $k \ge 0$,

$$\begin{split} \mathbb{H}_{h}^{\mathbf{t}} &:= \left\{ \mathbf{s}_{h} \in \mathbb{L}_{t\mathbf{r}}^{2}(\Omega) : \quad \mathbf{s}_{h} \big|_{T} \in \mathbb{P}_{k}(T) \quad \forall \ T \in \mathcal{T}_{h} \right\}, \\ \mathbb{H}_{h}^{\boldsymbol{\sigma}} &:= \left\{ \boldsymbol{\tau}_{h} \in \mathbb{H}_{0}(\mathbf{div};\Omega) : \quad \mathbf{c}^{\mathbf{t}} \boldsymbol{\tau}_{h} \big|_{T} \in \mathbf{RT}_{k}(T) \quad \forall \ \mathbf{c} \in \mathbb{R}^{2}, \ \forall \ T \in \mathcal{T}_{h} \right\}, \\ \mathbf{H}_{h}^{\mathbf{u}} &:= \left\{ \mathbf{v}_{h} \in \mathbf{C}(\bar{\Omega}) : \quad \mathbf{v}_{h} \big|_{T} \in \mathbf{P}_{k+1}(T) \quad \forall \ T \in \mathcal{T}_{h} \right\}, \\ \mathbf{H}_{h}^{\boldsymbol{\zeta}} &:= \left\{ \boldsymbol{\chi}_{h} \in \mathbf{L}^{2}(\Omega) : \quad \boldsymbol{\chi}_{h} \big|_{T} \in \mathbf{P}_{k}(T) \quad \forall \ T \in \mathcal{T}_{h} \right\}, \\ \mathbf{H}_{h}^{\mathbf{p}} &:= \left\{ \mathbf{q}_{h} \in \mathbf{H}_{N}(\mathrm{div};\Omega) : \quad \mathbf{q}_{h} \big|_{T} \in \mathbf{RT}_{k}(T) \quad \forall \ T \in \mathcal{T}_{h} \right\}, \\ \mathbf{H}_{h}^{\varphi} &:= \left\{ \psi_{h} \in \mathbf{C}(\bar{\Omega}) : \quad \psi_{h} \big|_{T} \in \mathbf{P}_{k+1}(T) \quad \forall \ T \in \mathcal{T}_{h} \right\}, \end{split}$$

which constitute an approximation of lower cost than those of existing competing schemes for this set of variables. It can be proved that for these spaces, the resulting methods are optimally convergent at a rate $\mathcal{O}(h^{k+1})$ (as long as the exact solutions are sufficiently smooth; see, e.g., [1, Lemma 5.5]). Notice also that, since $\boldsymbol{\sigma}$ is symmetric at a continuous level, its approximation $\boldsymbol{\sigma}_h$ is asymptotically symmetric as $h \to 0$. Indeed, by adding and subtracting $\boldsymbol{\sigma} = \boldsymbol{\sigma}^t$, there exists $\hat{C} > 0$ such that

$$\left\|\boldsymbol{\sigma}_{h}-\boldsymbol{\sigma}_{h}^{\mathsf{t}}\right\|_{0,\Omega}\leq 2\left\|\boldsymbol{\sigma}-\boldsymbol{\sigma}_{h}\right\|_{0,\Omega}\leq \widehat{C}\left\|\left(\vec{\mathsf{t}},\vec{\boldsymbol{\zeta}}\right)-\left(\vec{\mathsf{t}}_{h},\vec{\boldsymbol{\zeta}}_{h}\right)\right\|,$$

and then this quantity can be bounded using the Céa's estimate (3.6). Therefore, a rate of $\mathcal{O}(h^{k+1})$ can also be expected for the error decay of the symmetry of σ_h .

4 Numerical Examples

We now present some numerical results that confirm the accuracy of the proposed augmented mixed finite element methods (AMFEM). We also address how the absence of vorticity and the ultra-weak imposition of symmetry influence the quality of approximation. First, we define the individual errors

$$e(\mathbf{t}) := \| \mathbf{t} - \mathbf{t}_h \|_{0,\Omega}, \quad e(\boldsymbol{\sigma}) := \| \boldsymbol{\sigma} - \boldsymbol{\sigma}_h \|_{\operatorname{\mathbf{div}};\Omega}, \quad e(\mathbf{u}) := \| \mathbf{u} - \mathbf{u}_h \|_{1,\Omega},$$
$$e(\boldsymbol{\zeta}) := \| \boldsymbol{\zeta} - \boldsymbol{\zeta}_h \|_{0,\Omega}, \quad e(\mathbf{p}) := \| \mathbf{p} - \mathbf{p}_h \|_{\operatorname{\mathbf{div}};\Omega}, \quad e(\varphi) := \| \varphi - \varphi_h \|_{1,\Omega},$$

as well as their corresponding rates of convergence

$$r(\star) := \frac{\log(e(\star)/e'(\star))}{\log(h/h')} \quad \forall \star \in \big\{ \mathbf{t}, \boldsymbol{\sigma}, \mathbf{u}, \boldsymbol{\gamma}, \boldsymbol{\zeta}, \mathbf{p}, \varphi \big\},$$

where h and h' denote two consecutive meshsizes with errors e and e'. We also measure the symmetry of the stress tensors as

$$e_{\texttt{sym}} := \left\| \, \boldsymbol{\sigma}_h - \boldsymbol{\sigma}_h^\texttt{t} \, \right\|_{0,\Omega}, \quad r_{\texttt{sym}} := \frac{\log(e_{\texttt{sym}}/e_{\texttt{sym}}')}{\log(h/h')}.$$

DOF	h	$e(\boldsymbol{\sigma})$	$r(oldsymbol{\sigma})$	$e(\mathbf{u})$	$r(\mathbf{u})$	$e_{\mathtt{sym}}$	$r_{\tt sym}$	
			k =	= 0				
2,968	0.4332	7.7342	—	1.253	—	0.2226	—	
$9,\!454$	0.2887	5.2691	0.9464	0.7196	1.3672	0.1416	1.1162	
21,772	0.2165	3.9773	0.9781	0.4798	1.4090	0.1043	1.0630	
41,794	0.1732	3.1897	0.9897	0.3487	1.4319	0.0810	1.1314	
$71,\!392$	0.1443	2.6642	0.9949	0.2695	1.4134	0.0651	1.1946	
$112,\!438$	0.1237	2.2810	0.9975	0.2186	1.3561	0.0538	1.2447	
$166,\!804$	0.1083	1.9962	0.9988	0.1847	1.2651	0.0453	1.2835	
$236,\!362$	0.0962	1.7744	0.9996	0.1613	1.1487	0.0384	1.3145	
			k =	= 1				
$13,\!420$	0.4332	0.3036	—	0.1771	—	0.1286	_	
$43,\!528$	0.2887	0.1441	1.8333	0.1132	1.3103	0.0676	1.6584	
$101,\!140$	0.2165	0.0847	1.8457	0.0018	1.5675	0.0415	1.7697	
$195,\!184$	0.1732	0.0384	1.9832	0.0003	1.9431	0.0153	1.9138	
$334{,}588$	0.1443	0.0110	1.9906	0.0001	1.8795	0.0044	1.9581	

Table 4.1: Example 1. Error history for the vorticity-free AMFEM using first and second-order approximations.

4.1 Linear elasticity in the nearly incompressible limit

In this section we conduct numerical experiments in similar to those in [13, Tests 1 & 2]. Both problems involve three-dimensional domains, and given the Young modulus E = 1 and a Poisson ratio ν , we consider the following Lamé parameters:

$$\mu := \frac{E}{2(1+\nu)}$$
 and $\lambda := \frac{E\nu}{(1+\nu)(1-2\nu)}.$

Example 1. First, we set $\Omega = (0, 1)^3$, $\nu = 0.4900$ (that is, $\mu = 0.3356$ and $\lambda = 16.4430$) and source terms such that a closed-form solution to (2.4) is given by

$$\boldsymbol{\sigma} = \mathscr{C} \mathbf{e}(\mathbf{u}), \quad \mathbf{u} = \ell (x^2 + 1)(y^2 + 1)(z^2 + 1) \exp(x + y + z) \begin{pmatrix} 1\\1\\1 \end{pmatrix},$$

with $\ell = 0.04$. Note that the exact stress does not satisfy the condition $\int_{\Omega} \operatorname{tr}(\boldsymbol{\sigma}) = 0$. Nevertheless, here and in all subsequent tests, we can impose the condition $\int_{\Omega} \operatorname{tr}(\boldsymbol{\sigma}) = \int_{\Omega} \operatorname{tr}(\boldsymbol{\sigma}_{\text{exact}})$ by means of a real Lagrange multiplier (accounting for augmenting the resulting linear systems with one row and one column), see e.g. [13, Eq. (4.11)].

Example 2. We next focus on the three-dimensional L-shaped domain $\Omega = (-0.5, 0.5) \times (0, 1) \times (-0.5, 0.5) \setminus \{(0, 0.5) \times (0, 1) \times (0, 0.5)\}, \nu = 0.4999$ (giving $\mu = 0.3333$ and $\lambda = 1666.4444$) and define source terms such that the exact solution to (2.4) is the Kelvin fundamental solution

$$\boldsymbol{\sigma} = \mathscr{C}\mathbf{e}(\mathbf{u}), \quad \mathbf{u} = \frac{A}{r^3} \begin{pmatrix} (x - 0.25)^2 \\ (x - 0.25)(y - 0.5) \\ (x - 0.25)(z - 0.25) \end{pmatrix} + \frac{B}{r} \begin{pmatrix} 1 \\ 0 \\ 0 \end{pmatrix},$$

where $A = \frac{1}{16\pi\mu(1-\nu)}, B = \frac{3-4\nu}{16\pi\mu(1-\nu)}$ and $r = \left[(x - 0.25)^2 + (y - 0.5)^2 + (z - 0.25)^2 \right]^{1/2}$.

We show in Tables 4.1 and 4.2 a convergence history on a set of quasi-uniform refinements for each of the exact aforementioned solutions. Since these are smooth, the AMFEM with ultra-weakly

DOF	h	$h = e(\boldsymbol{\sigma})$		$e(\mathbf{u})$	$r(\mathbf{u})$	$e_{\mathtt{sym}}$	r_{sym}							
k = 0														
2,530	0.5349	1.0631	_	0.7136	_	0.7811	_							
4,600	0.3685	0.3228	1.8539	0.3452	1.9428	0.2514	1.8042							
$11,\!995$	0.2625	0.1519	1.2443	0.2359	1.1238	0.1566	1.2396							
24,265	0.1991	0.1143	1.0083	0.1908	0.8662	0.1154	1.1042							
$45,\!655$	0.1639	0.0931	1.0485	0.1613	0.9661	0.0956	0.9655							
$73,\!876$	0.1382	0.0763	1.1671	0.1357	1.0140	0.0774	1.1239							
113,146	0.1207	0.0665	1.0115	0.1205	0.9737	0.0679	0.9712							
			k =	: 1										
11,194	0.5349	0.5322	_	0.4926	_	0.4788	_							
20,932	0.3685	0.1168	1.7591	0.2163	1.8482	0.2112	1.9271							
$55,\!258$	0.2625	0.0387	1.8568	0.0585	1.8956	0.0557	2.1343							
112,882	0.1991	0.0172	1.9443	0.0268	2.0819	0.0219	2.1108							
213,274	0.1639	0.0108	2.0386	0.0182	1.9860	0.0133	2.0493							

Table 4.2: Example 2. Decay of the Cauchy stress, displacement, and symmetry errors produced by the vorticity-free AMFEM with first and second-order approximations.



Figure 4.1: Example 1. Velocity magnitude plotted on the deformed configuration, and XY - YX components of the Cauchy stress. The skeleton mesh is displayed on the undeformed geometry.

imposed symmetry converges at $\mathcal{O}(h^{k+1})$ (as expected from the previous section) when the finite element $(\mathbb{H}_h^{\sigma}, \mathbf{H}_h^{\mathbf{u}})$ from Section 3.3 is used. Moreover, as the vorticity has been removed from the system, the overall rate of convergence (dictated by the decay of the stress error) is slightly higher than in [13] (see also Table 4.3, below). Sample solutions are provided in Figure 4.1, where we can see that the off-diagonal components of the Cauchy stress practically coincide. The same behavior occurs for Example 2, as evidenced in Figure 4.2.

Perhaps one of the key differences of this method with respect to [13] is the reduction in degrees of freedom (DOF) and how symmetric the stress tensor is. Since the skew-symmetric vorticity tensor can be fully described with only 3 components, the reduction in 3 DOFs per element (when using a approximation by piecewise constant polynomials) with respect to the method in [13] is clear. This is confirmed further by portraying on Table 4.3 DOFs and symmetry errors associated with the method from [13] (focusing again on Example 1). The ultra-weak imposition leads to a comparable symmetry error (by observing again the values from the top block of Table 4.1), and both errors decay with $\mathcal{O}(h^{k+1})$, as expected.



Figure 4.2: Example 2. Velocity magnitude plotted on the deformed configuration, and XY - YX components of the Cauchy stress. The skeleton mesh is displayed on the undeformed geometry.

DOF	DOF	m	$\widetilde{\text{DOF}}/m$	DOF/m	$\widetilde{e(\boldsymbol{\sigma})}$	$\widetilde{r(\boldsymbol{\sigma})}$	$\widetilde{e_{\texttt{sym}}}$	$\widetilde{r_{\texttt{sym}}}$
4,120	2,968	384	10.73	7.721	7.7932	—	0.9664	—
13,342	$9,\!454$	$1,\!296$	10.29	7.294	5.4342	0.891	0.7213	0.8305
30,988	21,772	$3,\!072$	10.09	7.087	4.0173	1.048	0.5056	1.0343
59,794	41,794	6,000	9.962	6.996	3.2033	1.015	0.2835	1.0593
$102,\!496$	71,392	10,368	9.881	6.892	2.6674	1.004	0.1563	1.1235

Table 4.3: Example 1. Error history for the lowest-order augmented FEM from [13]. Here m is the number of tetrahedra in each mesh. The quantities without tildes denote DOFs and ratios associated with the proposed vorticity-free AMFEM. The reduction in 3 DOFs per element is clear.

4.2 The Boussinesq problem in two and three dimensions

We now turn to the numerical verification of the properties of the vorticity-free AMFEM presented in (3.5). We follow the experiments in [1] to show that this new method provides comparable results, at a lower computational cost.

Example 3. Here, $\Omega = (-1, 1)^2$, $\Gamma_D = [-1, 1] \times \{-1, 1\}$, $\Gamma_N = \Gamma \setminus \Gamma_D$, and we consider viscosity, thermal conductivity and body force as

$$\mu(\varphi) = \exp(-0.25\,\varphi), \quad k(\varphi) = \exp(0.25\,\varphi), \quad \mathbf{g} = (0,1)^{t},$$

where source terms f^{m} , f^{e} and boundary conditions are prescribed in such a way that the exact solution to (2.16) is given by

$$\mathbf{u} = \begin{pmatrix} 2y\sin(\pi x)\sin(\pi y)(x^2 - 1) + \pi\sin(\pi x)\cos(\pi y)(x^2 - 1)(y^2 - 1) \\ -2x\sin(\pi x)\sin(\pi y)(y^2 - 1) - \pi\cos(\pi x)\sin(\pi y)(x^2 - 1)(y^2 - 1), \end{pmatrix}, \quad \mathbf{t} = \mathbf{e}(\mathbf{u}),$$

$$\varphi = -0.6944 \, y^4 + 1.6944 \, y^2, \quad \boldsymbol{\sigma} = \mu(\varphi)\mathbf{t} - \mathbf{u} \otimes \mathbf{u} - (y^2 - x^2)\mathbb{I}, \quad \boldsymbol{\zeta} = \nabla\varphi, \quad \mathbf{p} = k(\varphi)\boldsymbol{\zeta} - \varphi\mathbf{u}$$

In addition, bounds for the physical properties are estimated in $\mu_1 = 0.5$, $\mu_2 = 1.25$, $k_1 = 0.75$ and $k_2 = 1.3$ and the Picard algorithm starts with $(\mathbf{u}, \varphi) = (\mathbf{0}, 0)$.



Figure 4.3: Example 3. XX component of the strain rate, pseudostress magnitude, XY and YX components of the pseudostress, velocity, temperature gradient, total heat flux, and temperature, computed with a first-order scheme associated with 68,356 DOF.

Example 4. Finally, we consider $\Omega = (0,1)^3$, $\Gamma_D = [0,1]^2 \times \{0\}$, $\Gamma_N = \Gamma \setminus \Gamma_D$, viscosity, thermal conductivity and body force as

$$u(\varphi) = 2.0 - 0.5 \, \varphi^2 - 0.5 \, \varphi^4, \quad k(\varphi) = -0.5 + 2.0 \, \mu(\varphi), \quad \mathbf{g} = (0, 0, 1)^{\texttt{t}},$$

and source terms and boundary conditions such that the exact solution is given by

$$\mathbf{u} = \begin{pmatrix} 8x^2yz(x-1)^2(y-1)(z-1)(y-z) \\ -8xy^2z(x-1)(y-1)^2(z-1)(x-z) \\ 8xyz^2(x-1)(y-1)(z-1)^2(x-y), \end{pmatrix}, \quad \varphi = \sin(\pi x)^2\sin(\pi y)^2(z-1)^2,$$
$$\mathbf{t} = \mathbf{e}(\mathbf{u}), \quad \boldsymbol{\sigma} = \mu(\varphi)\mathbf{t} - \mathbf{u} \otimes \mathbf{u} - (x-0.5)^3\sin(y+z)\mathbb{I}, \quad \boldsymbol{\zeta} = \nabla\varphi, \quad \mathbf{p} = k(\varphi)\boldsymbol{\zeta} - \varphi\mathbf{u}$$

The bounds for the physical properties are estimated in this case as $\mu_1 = 1.0$, $\mu_2 = 2.0$, $k_1 = 1.5$ and $k_2 = 3.5$, and the Picard algorithm starts with $(\mathbf{u}, \varphi) = (\mathbf{0}, 0)$.

In Tables 4.4 and 4.5 we can observe that when using the finite element $(\mathbb{H}_{h}^{t}, \mathbb{H}_{h}^{\sigma}, \mathbf{H}_{h}^{u}, \mathbf{H}_{h}^{\zeta}, \mathbf{H}_{h}^{p}, \mathbf{H}_{h}^{\varphi})$ from Section 3.3 with k = 0 and k = 1, the vorticity-free AMFEM converges at a rate $\mathcal{O}(h^{k+1})$. The reduction in DOF for this scheme is clear, but more importantly, it can also be seen that this does not lead to an increase of fixed-point iterations. Similarly to [1], a solution with a tolerance of 10^{-8} can be achieved for these problems in less than 10 Picard steps. Sample solutions for Examples 3 and 4 are displayed in Figures 4.3 and 4.4.

References

[1] J.A. ALMONACID AND G.N. GATICA, A fully-mixed finite element method for the Boussinesq problem with temperature-dependent parameters. Comput. Methods Appl. Math. (2019), in press.

Augmented mixed method with k = 0

DOF	י		h	e	$e(\mathbf{t})$	e	$(\boldsymbol{\sigma})$	ϵ	$e(\mathbf{u})$	ϵ	$e(\boldsymbol{\zeta})$	ϵ	(\mathbf{p})	e	e(arphi)	ϵ	sym
108		1.	4140	12	2.872	43	8.892	19	9.922	3.	3349	5.	7051	5.	8226	6.	3685
372		0.	7071	9.	0262	29	0.189	16	5.431	1.	7892	5.	6377	4.	4035	4.	1118
1,380)	0.	3536	5.	6625	17	7.016	1().832	1.	1887	4.	5898	2.	7744	3.	8566
5,316	3	0.	1768	3.	1263	8.	8880	5.	4914	0.	5501	2.	6782	1.	5790	2.	1146
20,86	68	0.	0884	1.	5659	4.	5021	2.	6512	0.	2438	1.	3671	0.	8343	1.	0861
82,69	92	0.	0442	0.	7779	2.	2675	1.	2996	0.	1159	0.	6783	0.	4301	0.	5337
329,2	220	0.	0221	0.	3875	1.	1313	0.	6437	0.	0570	0.	3376	0.	2184	0.	2513
	ite	er	$r(\mathbf{t})$)	$r(\boldsymbol{\sigma})$)	$r(\mathbf{u}$)	$r(\boldsymbol{\zeta})$)	$r(\mathbf{p})$)	$r(\varphi$)	r_{syn}	n	
	10)	_		_				_				_		_		
	10)	0.511	17	0.592	29	0.279	92	0.898	83	0.016	52	0.412	23	0.484	15	
	10)	0.672	27	0.774	16	0.60	12	0.590	01	0.294	16	0.666	67	0.664	15	
	10)	0.856	68	0.936	35	0.978	85	1.11	14	0.782	29	0.821	16	0.865	54	
	9		0.998	36	0.981	L1	1.052	27	1.174	48	0.973	31	0.911	17	0.969	91	
	9		1.008	31	0.994	15	1.029	96	1.072	27	1.009	91	0.955	59	1.013	38	
	9		1.005	53	0.998	32	1.014	46	1.022	23	1.007	74	0.978	81	1.035	54	

Augmented mixed method with k = 1

DOF	h	$e(\mathbf{t})$	$e(\boldsymbol{\sigma})$	$e(\mathbf{u})$	1)	$e(oldsymbol{\zeta})$		$e(\mathbf{p})$	e(arphi)	$e_{\mathtt{sym}}$
316	1.4140	7.258	19.74	1 11.4	48	1.312		2.93	3.045	4.891
1,156	0.7071	2.341	6.231	4.70	67	0.4386		1.69	1.143	1.751
4,420	0.3536	0.662	1.702	2 1.3	55	0.1413		0.3992	0.2598	0.69
17,284	0.1768	0.1781	0.444	$2 \mid 0.35$	34	0.03768		0.1014	0.06594	0.2064
68,356	0.0884	0.04578	0.112	$8 \mid 0.089$	921 (0.00965	55	0.02574	0.01676	0.05545
271,876	0.0442	0.01156	0.0288	$31 \mid 0.022$	237	0.00244	4 (0.006488	0.00423	0.01417
	iter	$r(\mathbf{t})$	$r(\boldsymbol{\sigma})$	$r(\mathbf{u})$	$r(\boldsymbol{\zeta})$) r((\mathbf{p})	$r(\varphi)$	r_{sym}	
	9	_	_	_	-		_	_	_	
	9	1.6325	1.6649	1.2683	1.581	18 0.7	7938	1.4147	1.4852	
	9	1.8228	1.8726	1.8159	1.634	43 2.0)822	2.1373	1.6453	
	9	1.8949	1.9383	1.9396	1.907	72 1.9	9774	1.9781	1.7421	
	9	1.9656	1.9784	1.9861	1.965	59 1.9	9797	1.9765	1.8966	
	9	1.9867	1.9693	1.9954	1.98	57 1.9	9889	1.9860	1.9648	

Table 4.4: Example 3. Convergence history and Picard iteration count for the vorticity-free AMFEM applied to the Boussinesq equations in 2D.

- [2] J.A. ALMONACID, G.N. GATICA AND R. OYARZÚA, A mixed-primal finite element method for the Boussinesq problem with temperature-dependent viscosity, Calcolo 55 (2018), no. 3, Art. 36, 42 pp.
- [3] J.A. ALMONACID, G.N. GATICA, R. OYARZÚA AND R. RUIZ-BAIER, A new mixed finite element method for the n-dimensional Boussinesq problem with temperature-dependent viscosity, Preprint 2018-18, Centro de Investigacion en Ingenieria Matematica (CI²MA), Universidad de Concepcion, Chile, (2018).
- [4] M. ALVAREZ, G.N. GATICA, B. GOMEZ-VARGAS AND R. RUIZ-BAIER, New mixed finite element methods for natural convection with phase-change in porous media, J. Sci. Comput. (2019), in press.
- [5] D.N. ARNOLD, F. BREZZI AND J. DOUGLAS, PEERS: A new mixed finite element for plane elasticity. Japan J. Appl. Math. 1 (1984), 347–367.

Augmented mixed method with k = 0

DOF			h	e	(t)	$e(\boldsymbol{\sigma})$		e	$e(\mathbf{u})$		$e(\boldsymbol{\zeta})$		$e(\mathbf{p})$		$e(\varphi)$		e _{sym}
153		1.0)322	0.4	4303	5.5768 0		0.2	2308 0.8		3549	22	2.737	6	.0623	0	.7802
3,065	5	0.5	5774	0.1	1128	2.2324		0.1	1479	2.5	.5377 11		.8923	2	.3667	7	.5091
13,46	55	0.3	3464	0.0	0.0383		1.0762		0.0356		0.7871		2175	1	.2359	0	.0604
36,15	53	0.2	2474	0.0	0161	0.8	8179	0.0	0184	0.3587		5.2149		0.8593		0	.0359
75,92	29	0.1	1925	0.0	0100	0.6	6477	0.0	0132	0.2	2661	4.	0870	0.6752		0	.0256
137,5	693	0.1	1575	0.0	0073	0.5	5341	0.0	0105	0.2	2203	3.	3563	0	.5573	0	.0199
225,9	945	0.1	1332	0.0	0057	0.4	4538	0.0	0088	0.1	911	2.	8454	0	.4749	0	.0104
345,7	785	0.1	155	0.0	0047	0.3	3942	0.0	0076	0.1	1701	2.	4687	0	.4142	0	.0139
501,9	013	0.1	1019	0.0	0041	0.5	3483	0.0	0064	0.1	1541	2.	1831	0	.3675	0	.0120
	ite	ər	$r(\mathbf{t}$;)	$r(\boldsymbol{\sigma}$	-)	$r(\mathbf{u})$	I)	$r(\boldsymbol{\zeta})$	·)	$r(\mathbf{p}$)	$r(\varphi)$)	$r_{\mathtt{sym}}$	ı	
	7	,	-		_		–		-		_		_		-		
	7	,	1.14	19	0.79	61	1.36	55	1.03	57	0.88	46	0.916	52	0.638	36	
	8		1.24	62	1.08	32	1.84	90	1.26	81	1.21	27	1.709)1	0.898	31	
	8		1.35	83	0.81	56	1.25	49	1.23	59	0.96	47	1.082	$24 \mid 1.254$		19	
	8		1.28	1.2885		$0.9291 \mid 1.32$		45	1.1892		0.9626		0.9600		1.2342		
			1.25	87	0.9607 1.13		$23 \mid 0.9408$		08	0.9812				1.1253			
			1.21	41	11 0.9757		$7 \mid 1.0550 \mid 1.0254$		0.85	0.987 + 0.987		$(3 \mid 0.956)$		59	9 1.118		
			1.12	92	0.98	0.9843 1.03		$34 \mid 0.910$		09	0.99	07	0.956	56	1.1420		
	1		1.12	08	0.98	91	1.00	25	0.98	99	0.99	29	0.95	6	1.11()3	
					Augm	ent	ed mi	xed	meth	od	with	k =	- 1				
DOI	<u>۲</u>		h		$e(\mathbf{t})$	$e(\boldsymbol{\sigma})$		$e(\mathbf{u}) = e(\mathbf{u})$		$e(oldsymbol{\zeta}) = \epsilon$		$e(\mathbf{p})$		$e(\varphi)$	$e_{\texttt{sym}}$		
589		1.	7326	0.	0262)262 5.7147		0.0310		0.9276		1.3559		1.	0891	0.	0004
13,0	37	0.	5774	0.	0074	0.	1622	0.	0078	0.	2089	0.	7459	0.2749		0.	0144
58,12	25	0.	3464	0.	0018	0.	0553	0.	0033	0.	0738	0.	2571	0.	1011	0.	0058
156,	973	0.	2474	0.	0007	0.	0208	0.	0019	0.	0358	0.	1225	0.	0487	0.	0031
330,	701	0.	1925	0.	0003	0.	0095	0.	0011	0.	0194	0.	0664	0.	0283	0.	0019
600,	429	0.	1575	0.	0001	0.	0050	0.	0005	0.	0125	0.	0430	0.	0185	0.	0011
	ite	ər	$r(\mathbf{t})$		$r(\boldsymbol{\sigma})$	-)	$r(\mathbf{u})$	1)	$r(\boldsymbol{\zeta})$)	$r(\mathbf{p}$)	$r(\varphi)$)	r_{sym}	1	
	8	8 -			-			-	_	~	_	~-					
	8 1.92		71	2.20	42	1.64	73	$ 1.83 \\ 2.22$	57	2.24	97 97		23		19		
			1.76	96	2.10	48	1.69	010	2.03	36	2.08	35	1.958	53	1.773	36	
			1.90	108 E 4	2.19	UI 15	1.83	99	2.14	24 79	2.12	04 20	$\begin{bmatrix} 2.163\\ 0.166 \end{bmatrix}$	58 34	1.853	55 20	
	9		1.94	:04 20	2.13	10 01	1.89	51 00	$\begin{bmatrix} 2.44 \\ 2.19 \end{bmatrix}$	(2 01	2.14	52 50	2.100)4)5	1.890)9 (9	
	8	8 1.9530		30	2.10	2.1081 1.918		02	2 2.1891		2.1650) 2.0925		1.9253		

Table 4.5: Example 4. Convergence history and Picard iteration count for the vorticity-free AMFEM applied to the Boussinesq equations in 3D.

- [6] J. CAMAÑO, R. OYARZÚA, R. RUIZ-BAIER AND G. TIERRA, Error analysis of an augmented mixed method for the Navier-Stokes problem with mixed boundary conditions, IMA J. Numer. Anal. 38 (2018), no. 3, 1452–1484.
- [7] E. COLMENARES, G.N. GATICA AND R. OYARZÚA, Analysis of an augmented mixed-primal formulation for the stationary Boussinesq problem. Numer. Methods Partial Differential Equations 32 (2016), no. 2, 445–478.
- [8] E. COLMENARES, G.N. GATICA AND R. OYARZÚA, An augmented fully-mixed finite element method for the stationary Boussinesq problem. Calcolo 54 (2017), no. 1, 167–205.



Figure 4.4: Example 4. Strain rate magnitude, pseudostress magnitude, velocity streamlines, temperature gradient, total flux, and temperature, computed with a first-order scheme associated with 345,785 DOF.

- [9] B.X. FRAEJIS DE VEUBEKE, *Stress function approach*. World Congress on the Finite Element Method in Structural Mechanics, Bournemouth, 1975.
- [10] G.N. GATICA, Analysis of a new augmented mixed finite element method for linear elasticity allowing $\mathbb{RT}_0 \mathbb{P}_1 \mathbb{P}_0$ approximations, M2AN Math. Model. Numer. Anal. 40 (2006), no. 1, 1–28.
- [11] G.N. GATICA, An augmented mixed finite element method for linear elasticity with non-homogeneous Dirichlet conditions, Electron. Trans. Numer. Anal 26 (2007), 421–438.
- [12] G.N. GATICA, A Simple Introduction to the Mixed Finite Element Method: Theory and Applications. Springer Briefs in Mathematics, Springer, Cham, 2014.
- [13] G.N. GATICA, A. MÁRQUEZ AND S. MEDDAHI, An augmented mixed finite element method for 3D linear elasticity problems, J. Comput. Appl. Math. 231 (2009), no. 2, 526–540.
- [14] W. MCLEAN, Strongly Elliptic Systems and Boundary Integral Equations, Cambridge University Press, New York, 2000.
- [15] R. STENBERG, A family of mixed finite element methods for the elasticity problem. Numer. Math. 53 (1988), 513–538.